# Labino® Torch Light Spotlight



#### MAKES IT BRIGHT

## 365 nm | HIGH-POWER | SMALL

- The Labino<sup>®</sup> Torch Light Spotlight is a smallsized, lightweight, UV-A LED flashlight designed for quick inspections and access to "hard-toreach" spots.
- The lamp measures 14.5 cm long (5.7 inches) and weighs 145 gram (5.1 oz), battery included.
- The Labino<sup>®</sup> Torch Light Spotlight produces a narrow intense ultraviolet beam measuring over 8000 μw/cm² at a distance of 38 cm (15 inches).
- The Labino® Torch Light Spotlight contains one (1) ultraviolet light emitting diode (LED). The LED creates UV light that peaks at 365 nm making it suitable for industrial, leakage and security applications.
- Full power is reached instantly. The on/off button is recessed in the back of the lamp to prevent accidental activation.
- At full charge the battery provides up to 8 hours of use. Recharge from a normal outlet or vehicle with included chargers. The kit also includes an extra battery.



## **TECHNICAL SPECIFICATION**

## **UV LED**

- UV source: UV A LED (1)
- Intensity: > 8.000 μw/cm² at 38 cm (15 inches)
- Wave length: 365 nm
- Expected LED life: approx. 50,000 hours
- Distribution angle (beam): spotlight

## DISTRIBUTOR:

#### **Battery**

- 2200 mAh Lithium-lon, 3.7 volts
- Running time: approx. 8 hrs
- · Charging time: approx. 2 hrs
- Requires one (1) battery to operate

#### Charger

- One (1) 100-240 VAC charger for use from electrical outlet
- One (1) 12 V charger for use in vehicle via cigarette lighter connection
- Capacity: two batteries can be charged simultaneously

#### **Dimensions**

- Length: 14.5 cm ( 5.7 inches)
- Weight with battery: 145 gr (5.1 oz)

### Included in the Labino® Torch Light Kit

- UV LED flashlight
- Charger for use from electrical outlet
- Charger for use in vehicle via cigarette lighter connection
- Two (2) batteries (1+1 extra)
- The kit is available with or without a belt holster

Labino AB shall not be held liable for any errors or omissions resulting from the test procedures that were used in validating performance of any Labino AB product nor for unforeseen errors or omissions in digital or printed material.